


DOT MATRIX PRINTER
9-PIN NARROW CARRIAGE
LX-310

EPSON
 EXCEED YOUR VISION



**HIGHLY RELIABLE PRINTING
 WITH BETTER PERFORMANCE.**

Designed to be more efficient, Epson LX-310 offers extraordinary processing and print speed. This compact 9-pin performer not only prints up to 357 characters per second (12 characters per inch) in High Speed Draft Mode but also offers remarkable reliability. Epson's constant innovations in printing solutions give you the best performing printer that suits your fast paced environment.



ENGINEERED FOR BUSINESS

High Processing Speed

You can now enjoy high-speed processing time, with 128KB data buffer that will reduce waiting time.

Fast Print Speed

Maximize productivity with a fast print speed of up to 357 characters per second (12 cpi).


Long-life Reliability

With a Mean Time Between Failure (MTBF) rating of 10,000 POH (power on hours), it saves cost on electricity without compromising good quality printing.

MODEL NUMBER	LX-310		
Printing Technology	Impact dot matrix		
Print Method	9 pins		
Number of Pins in Head	Bi-direction with logic seeking		
Print Direction	ESC/P and IBM PPDS emulation		
Control Code			
Print Speed			
High Speed Draft	10 / 12 / 15 cpi	347 / 357 / 390 cps	
High Speed Draft Condensed	17 / 20 cpi	383 / 298 cps	
Draft	10 / 12 / 15 cpi	260 / 312 / 223 cps	
Draft Condensed	17 / 20 cpi	222 / 260 cps	
Draft Emphasized	10 cpi	130 cps	
NLQ	10 / 12 / 15 / 17 / 20 cpi	65 / 78 / 55 / 47 / 56 cps	
Print Characteristics			
Character Sets	Italic table, PC437 (US Standard Europe), PC850 (Multilingual), PC860 (Portugese), PC861 (Icelandic), PC863 (Canadian French), PC865 (Nordic), Abicomp, BRASCII, Roman 8, ISO Latin 1, PC 858, ISO 8859-15		
Bitmap Fonts	Epson Draft: 10, 12, 15 cpi; Epson Roman & Sans Serif: 10, 12, 15 cpi, Proportional;		
Barcode Fonts	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, Postnet		
Printable Columns			
Pitch	10 / 12 / 15 / 17 / 20 cpi	80 / 96 / 120 / 137 / 160 cpl	
Paper Handling			
Paper Path	Tractor	Rear in, Top out	
	Manual Insertion	Rear in, Top out	
Paper Size		Length	Width
Cut Sheet (Single Sheet)		100 ~ 364mm (3.9 ~ 14.3")	100 ~ 257mm (3.9 ~ 10.1")
Cut Sheet (Multi Part)		100 ~ 364mm (3.9 ~ 14.3")	100 ~ 257mm (3.9 ~ 10.1")
Envelope (No.6)		92mm (3.6")	165mm (6.5")
Envelope (No.10)		105mm (4.1")	241mm (9.5")
Continuous Paper		101.6 ~ 558.8mm (4.0 ~ 22.0")	101.6 ~ 254.0mm (4.0 ~ 10.0")
Roll Paper			216mm (8.5")
Paper Feeding			
Standard		Friction, Push Tractor	
Optional		Roll Paper Holder	
Copies		Original + 4 copies	
Line Spacing		4.23mm (1/6") or programmable in increments of 0.118mm (1/216")	
Input Data Buffer		128KB	
Interface			
Standard		Bi-directional parallel (IEEE-1284 nibble mode supported) USB 2.0 Full-Speed Serial	
Ribbon Cartridge			
Standard		Fabric Ribbon Cartridge (Black)	
Ribbon Life		Approx. 4.0 million characters (Draft 10 cpi, 14 dots/character)	
Acoustic Noise		Approx. 53 dB(A) (ISO 7779 pattern)	
Reliability			
Mean Print Volume Between Failure (MVBf)		Approx. 20 million lines (Except print head)	
Mean Time Between Failure (MTBF)		Approx. 10,000 POH (25% Duty)	
Print Head Life		Approx. 400 million strokes/wire	
Control Panel		4 switches and 5 LEDs	
Environmental Conditions (Operating)			
Temperature		5 ~ 35°C	
Humidity		10 ~ 80 % RH	
Electrical Specification			
Rated Voltage		AC 120 / 220 - 240V	
Rated Frequency		50Hz / 60Hz	
Power Consumption			
Operating		Approx. 27W (ISO/IEC 10561 Letter pattern), (ENERGY STAR compliant)	
Sleep Mode		Approx. 1.1W	
Auto Off Mode		Approx. 0.2W (120V), Approx. 0.3W (230V)	
Power Off		0W	
Printer Driver / Utility			
Operating System		Microsoft® Windows® 2000 / XP / 7, Microsoft® Windows Vista®	
Utility			
Epson Status Monitor 3		Microsoft® Windows® 2000 / XP / 7, Microsoft® Windows Vista®	
Epson Printer Setting		Microsoft® Windows® 2000 / XP / 7, Microsoft® Windows Vista®	

Dimensions & Weight

Weight: Approx. 4.1kg (9.0lb)



Options

Fabric Ribbon Cartridge (Black) S015632

Legend

- cpi Characters per inch (Characters per 25.4mm)
- cps Characters per second
- cpl Characters per line
- POH Power On Hours



© 2012 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Dealer's Stamp



Official Partner of Manchester United