

The simplest ways to Use!

LK-P24 LK-P34

2-Inch / 3-Inch
Mobile Receipt Printer
With Advanced Manual Cutter



KEY FEATURES



Simplicity to use

- By pushing a button up, Easily paper cut and resolve the paper jam problem.
- By pushing a button down, Conveniently open the cover and load the media.
- Supports NFC function for quick Bluetooth pairing with compatible devices.



Excellent compatibility

- Supports Wi-Fi(802.11 a/b/g/n) and Bluetooth 4.2 classic and Low energy.
- Simultaneously connect to multiple peripherals via Bluetooth 4.2 classic and Low Energy (BLE).
- MFi(Made for iPhone/iPAD) Certified.
- Compatible with Android, iOS and Windows operating systems.
- Supports major programming languages including ESC/POS, CPCL, ZPL.



High portability

- Dust and water-resistance rating : IP43(LK-P24), IP54(LK-P34)
- Supports various accessories including Belt clip(Strap), Shoulder strap and leather case etc.
- Quickly and conveniently recharge with battery cradles.



4Bay battery cradle
(Up to 4 batteries available)



Battery cradle



Set cradle
(4 cradles in 1 set)



LK-P24 / P34 2-Inch/3-Inch Mobile Receipt Printer

SPECIFICATIONS

MEDIA CHARACTERISTICS

Media Type

Thermal paper

Media Width

- LK-P24 : 2.2" (58mm)

- LK-P34 : 3.1" (80mm)

Media Core Diameter

0.4" (12.5mm)

Media Roll Diameter

1.5" (40mm)

Thickness

0.06mm

OPERATING CHARACTERISTICS

Operating Temperature

14~122°F(-10 ~ 50°C)

Operating Humidity

10 ~ 80%

Storage Temperature

-4~140°F(-20 ~ 60°C)

Storage Humidity

10 ~ 90%

Dust-and Water-resistance Rating

- LK-P24 : IP43

- LK-P34 : IP54

Drop Rating

5ft/1.5m (unit only) to concrete

AGENCY APPROVALS

KC, CE, FCC, UL/cUL, Mfi, Telec

PHISICAL CHARACTERISTICS

Dimension (W x D x H)

- LK-P24 :

3.2"×4.77"×1.78" (81.5x121.4x45.3mm)

- LK-P34 :

4.23"×5.70"×2.20" (107.5x145x56mm)

Weight (Kg)

- LK-P24 : 0.5lb(0.2kg, Battery Incl.)

- LK-P34 : 0.9lb(0.4kg, Battery Incl.)

SOFTWARE

Emulation

ESC/POS, CPCL, ZPL Command compatible

Driver

Windows Driver(10, 2012, 8, 7, 2008, VISTA,

2003, XP, 32bit & 64bit), Window CE &

Mobile Driver & SDK (CE 4.2~, Mobile 5.0~),

Linux Driver, Mac Driver,

OPOS Driver, JavaPOS Driver

SDK

iOS, Android(2.1~), Windows,

Linux, Blackberry, Symbian

BARCODE

1D

EAN-8, EAN-8(+2+5), EAN-13, EAN-13(+2+5), Codabar,

Code11, Code39, Code93, Code128, ITF, LUPC-A(+2+5),

UPC-E, UPC-E(+2+5), Planet, UPC-A etc

2D

QR, PDF417, MicroPDF417, Maxicode, Datamatrix,

Aztec, RSS14, TLC39

FONT / GRAPHICS

Character Size

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Japanese(24x24), Korean(24x24)

Characters per Line (CPL)

- LK-P24: Font A(12x24): 32cpl,

Font B(9x17): 42cpl,

Chinese / Korean / Japanese: 16cpl

- LK-P34: Font A(12x24): 48cpl,

Font B(9x17): 64cpl,

Chinese / Korean / Japanese: 24cpl

Character Set

95 Alphanumeric, 14 International, 128 x 18 Graphic

ACCESSORIES

Standard

- LK-P24 : Charger, USB Cable, Battery Pack,
Thermal Roll Paper, Belt Strap & Bracket

- LK-P34 : Charger, USB Cable, Battery Pack,
Thermal Roll Paper, Belt Strap

Option

- LK-P24 : Set Cradle, Leather Case + Shoulder Strap,
Belt Clip

- LK-P34 : 4bay Cradle, Battery Cradle, Shoulder Strap,
Belt Strap



Republic of Korea [Head Office]

28-6, Gajangsaneopdong-ro,
Osan-si, Gyeonggi-do, 18103,
Republic of Korea

T. +82-31-8077-5000

F. +82-31-624-5310

E. sales@miniprnter.com

México

Paseo de la Reforma No. 265 Piso 2.
Oficina SBC. Col. Cuauhtémoc,
C.P. 06500 Ciudad de Mexico

T. +52-1-55-3232-9543

E. sales@miniprnter.com

North America

20280 S. Vermont Ave. STE 200,
Torrance, CA 90502, USA

T. +1-310-561-8030

E. sales@miniprnter.com