

TOSHIBA

DESKTOP

BV400 series

- Compact & sleek design with a small footprint
- Intuitive & clear user experience with LCD models
- Direct thermal and thermal transfer models
- RFID encoding available with thermal transfer printers
- SOTI Connect certified for IoT device management





Discover a printer that's built for more.

Reliability designed to boost efficiency.

Designed to meet diverse needs, Toshiba's highly reliable barcode label printers help to simplify labeling tasks, guaranteeing accuracy and efficiency. Benefit from faster speeds, reduced downtime and lower operating costs thanks to their inclusion of the latest technology. And effortlessly integrate Toshiba barcode printers into complex IT environments using standard interfaces and optional Wi-Fi or Bluetooth.

Excellent design meets advanced connectivity.

Delivering the ultimate user experience, simplicity and efficiency are top of mind with the BV400 series. Combining a small, compact footprint with a sleek design, these printers ensure enhanced connectivity for seamless integration into various networks and print language emulations, easily adapting to almost every print scenario in an ever-changing workplace. Built to last, they deliver premium print quality and performance rivaling mid-range industrial printers.

Versatile solutions for varied workspaces.

Ergonomic and sleek, the BV400 series is ideal for small industry operations, shipping/receiving centers and small businesses that require robust labeling in compact spaces. The BV400 series is available in direct thermal or thermal transfer models with 203/300 dpi and black or white cabinets. Both models adapt seamlessly to diverse operating environments, from manufacturing to healthcare.



The reliable BV400 series is an ideal printing solution for demanding environments, such as:

- Transportation (shipping labels)
- Healthcare (wrist bands)
- Retail (shelf labels)

Advanced and adaptable labeling for challenging environments.

This compact printer packs a punch. Its sleek design takes up minimal space, while its intuitive interface and vast compatibility with languages and emulations makes every print job a breeze.

And you can print with confidence knowing your device is equipped for the future. This printer's SOTI Connect certification ensures seamless IoT integration and management, while optional RFID encoding with thermal transfer models provides the capabilities needed to accomplish the next level of process automation.



Ease of Use



Speed & Efficiency



Solid Reliability



RFID Encoding



IoT Device Management

Making print simple: An integrated LCD screen on BV410 models delivers clear information and color-coded notifications. Adjustments can be made on the printer, and full setup is possible remotely.

Printing at the speed of business: Market-leading print speeds up to 7 inches per second with a fast CPU allow for quick data processing, and instant readiness from power-on due to its rapid boot-time.

Built for rugged reliability: Designed for demanding environments, you're ensured smooth, worry-free operations day after day, while an optional built-in AC adapter delivers a tidy and safe workplace, and recessed ports ensure connectivity while in operation.

Advanced solutions with endless possibilities: RFID technology expands the BV410T's applications across various markets, streamlining operations and bringing data to your desktop, and the BV400 series offers advanced solutions typically reserved for industrial printers.

Empowering IoT device management: Adding support for SOTI Connect to Toshiba desktop printers enables businesses to trace large printer fleets and overcome printer management challenges, such as remote access for firmware updates and automated rule deployment.



BV400D

BV400T

BV400 series

BV400D series



Standard features

- 4" Desktop Direct Thermal
- 203 dpi, 300 dpi Models
- Flat Edge Print Head Design
- 128MB SDRAM, 128MB Flash ROM
- Maximum Print Speed - 7 ips
- Emulation Support: Zebra® ZPL II, Datamax® DPL, Sato® SBPL, EPL2, Intermec IPL
- Compact Footprint
- Easily Replaceable Print Heads and Consumables
- ENERGY STAR® Certified V3.2

Models	BV410D-GS (203 dpi)	BV410D-TS (300 dpi)	BV420D-GS (203 dpi) BV420D-GL (203 dpi) Linerless	BV420D-TS (300 dpi)
Printer Specification				
Technology	Direct Thermal	Direct Thermal	Direct Thermal	Direct Thermal
Print Head	Flat Head	Flat Head	Flat Head	Flat Head
Resolution	203 dpi (8 dots/mm)	300 dpi (11.8 dots/mm)	203 dpi (8 dots/mm)	300 dpi (11.8 dots/mm)
User Interface	2x LED, 3x key, with LCD	2x LED, 3x key, with LCD	3x LED, 2x key	3x LED, 2x key
Print Speed (Max)	7 ips (177.8 mm/sec)	5 ips (127 mm/sec)	7 ips (177.8 mm/sec)	5 ips (127 mm/sec)
Memory	128 SDRAM 128 Flash ROM	128 SDRAM 128 Flash ROM	128 SDRAM 128 Flash ROM	128 SDRAM 128 Flash ROM
Print Length (Max)	39.25" (997 mm)	39.25" (997 mm)	39.25" (997 mm)	39.25" (997 mm)
Print Width (Max)	4.25" (108 mm)	4.16" (105.7 mm)	4.25" (108 mm) (GS); 3.9" (99.6 mm) (GL)	4.16" (105.7 mm)
Media				
Alignment	Centered	Centered	Centered	Centered
Media Sensor	Reflective, Transmissive	Reflective, Transmissive	Reflective, Transmissive (GS) Reflective (GL)	Reflective, Transmissive
Media Length	0.32" - 39.25" Batch Mode, 0.92"-5.92" Strip Mode, 0.76"-39.1" Cut Mode	0.32" - 39.25" Batch Mode, 0.92"-5.92" Strip Mode, 0.76"-39.1" Cut Mode	0.32" - 39.25" Batch Mode, 0.92"-5.92" Strip Mode, 0.76"-39.1" Cut Mode	0.32" - 39.25" Batch Mode, 0.92"-5.92" Strip Mode, 0.76"-39.1" Cut Mode
Media Width	1.0" - 4.6" (25.4 mm - 118 mm)	1.0" - 4.6" (25.4 mm - 118 mm)	1.0" - 4.6" (25.4 mm - 118 mm) (GS) 1.26" - 4" (32 mm - 102 mm) (GL)	1.0" - 4.6" (25.4 mm - 118 mm)
Media Thickness	0.0024" - 0.0074" (0.06 mm - 0.19 mm)	0.0024" - 0.0074" (0.06 mm - 0.19 mm)	0.0024" - 0.0074" (0.06 mm - 0.19 mm)	0.0024" - 0.0074" (0.06 mm - 0.19 mm)
Media Format	Roll, Fanfold	Roll, Fanfold	Roll, Fanfold	Roll, Fanfold
Print				
Barcodes	UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN 128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, POSTNET, RM4SCC, KIX Code, Customer Barcode, GS1 DataBar, USPS Intelligent Mail Barcode			
2D Codes	Data Matrix, PDF 417, MaxiCode, QR Code, Micro PDF 417, Micro QR, GS1 Data Matrix, GS1 QR Code, Aztec Code			
Software & Connectivity				
Programming Language	Toshiba TPCL, Basic Command Interpreter (BCI)			
Emulations	Zebra® ZPL II, Datamax® DPL, Sato® SBPL, EPL2, Intermec IPL			
Printer Driver	Windows 11/10, Windows Server 2019/2016/ 2012 R2/2012, SAP, Linux, macOS			
Label Software	BarTender, UltraLite			
IoT Device Management	SOTI Connect			
Interface				
Standard	USB 2.0, Ethernet 10/100 Base-T			
Optional	WLAN 802.11a/b/g/n (Dual Band for 2.4 GHz/5 GHz) Bluetooth V2.1 EDR with MFi Certified, Serial Port (RS-232C)			
Accessories				
Standard			Linerless Cutter (GL)	
Optional	Full Cutter Module Partial Cutter Module Peel-off Module 8" External Media Stand Wireless LAN Kit Bluetooth Interface Kit Serial (RS-232C) I/F Kit AC Adapter Cover	Full Cutter Module Partial Cutter Module Peel-off Module 8" External Media Stand Wireless LAN Kit Bluetooth Interface Kit Serial (RS-232C) I/F Kit AC Adapter Cover	Full Cutter Module* Partial Cutter Module* Peel-off Module* 8" External Media Stand* Wireless LAN Kit Bluetooth Interface Kit Serial (RS-232C) I/F Kit AC Adapter Cover	Full Cutter Module Partial Cutter Module Peel-off Module 8" External Media Stand Wireless LAN Kit Bluetooth Interface Kit Serial (RS-232C) I/F Kit AC Adapter Cover
Fonts Standard	Built-in Fonts: Bitmap, Outline, Price, TTF (Optional), Writable Characters			
Environmental				
Operating Temperatures	41°F - 104°F (5°C - 40°C)			
Operating Humidity	25% to 85% RH (Non-condensing)			
Storage Temperature/ Humidity	-40° to 60°C (-40° to 140°F) / 10 to 90% non-condensing relative humidity (RH)			
Power Consumption	Printing Mode: 60W Standby Mode: 4.4 W			
Power Supply	AC 100 to 240 V, 50/60 Hz			
Dimension (W x H x D)	6.85" x 8.59" x 6.81" (174 mm x 218 mm x 173 mm)		6.85" x 8.59" x 6.81" (174 mm x 218 mm x 173 mm) (GS) 6.85" x 11.34" x 6.81" (174 mm x 288 mm x 173 mm) (GL)	6.85" x 8.59" x 6.81" (174 mm x 218 mm x 173 mm)
Weight	4.4 lb. (2.0 kg)		4.4 lb. (2.0 kg) (GS) 5.7 lb. (2.6 kg) (GL)	4.4 lb. (2.0 kg)
Weight Shipping	6.61 lb. (3.0 kg)		6.6 lb. (3.0 kg) (GS) 7.94 lb. (3.6 kg) (GL)	6.61 lb. (3.0 kg)

*Not an option for BV420D-GL02

BV400T series



Standard features

- 4" Desktop Thermal Transfer
- 203 dpi, 300 dpi Models
- Flat Edge Print Head Design
- 128MB SDRAM, 128MB Flash ROM
- Maximum Print Speed - 7 ips
- Emulation Support: Zebra® ZPL II, Datamax® DPL, Sato® SBPL, EPL2, Intermec IPL
- Compact Footprint
- Easily Replaceable Print Heads and Consumables
- ENERGY STAR® Certified V3.2

Models	BV410T-GS (203 dpi)	BV410T-TS (300 dpi)	BV420T-GS (203 dpi)	BV420T-TS (300 dpi)
Printer Specification				
Technology	Thermal Transfer	Thermal Transfer	Thermal Transfer	Thermal Transfer
Print Head	Flat Head	Flat Head	Flat Head	Flat Head
Resolution	203 dpi (8 dots/mm)	300 dpi (11.8 dots/mm)	203 dpi (8 dots/mm)	300 dpi (11.8 dots/mm)
User Interface	2x LED, 3x key, with LCD	2x LED, 3x key, with LCD	3x LED, 2x key	3x LED, 2x key
Print Speed (Max)	7 ips (177.8 mm/sec)	5 ips (127 mm/sec)	7 ips (177.8 mm/sec)	5 ips (127 mm/sec)
Memory	128 SDRAM 128 Flash ROM	128 SDRAM 128 Flash ROM	128 SDRAM 128 Flash ROM	128 SDRAM 128 Flash ROM
Print Length (Max)	39.29" (997.9 mm)	39.29" (997.9 mm)	39.29" (997.9 mm)	39.29" (997.9 mm)
Print Width (Max)	4.25" (108 mm)	4.16" (105.7 mm)	4.25" (108 mm)	4.16" (105.7 mm)
Media				
Alignment	Centered			
Media Sensor	Reflective, Transmissive			
Media Length	0.24" - 39.29" Batch Mode, 0.8"-39.29" Cut Mode, 0.84"-5.84" Peel-off Mode			
Media Width	1.0"- 4.7" (25.4 mm - 118 mm)			
Media Thickness	.0024" - .0074" (.06 mm - 0.19 mm)			
Media Format	Roll, Fanfold			
Print				
Barcodes	UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN 128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, POSTNET, RM4SCC, KIX Code, Customer Barcode, GS1 DataBar, USPS Intelligent Mail Barcode			
2D Codes	Data Matrix, PDF 417, MaxiCode, QR Code, Micro PDF 417, Micro QR, GS1 Data Matrix, GS1 QR Code, Aztec Code			
Software & Connectivity				
Programming Language	Toshiba TPCL, Basic Command Interpreter (BCI)			
Emulations	Zebra® ZPL II, Datamax® DPL, Sato® SBPL, EPL2, Intermec IPL			
Printer Driver	Windows 11/10, Windows Server 2019/2016/ 2012 R2/2012, SAP, Linux, macOS			
Label Software	BarTender, UltraLite			
IoT Device Management	SOTI Connect			
Interface				
Standard	USB 2.0, Ethernet 10/100 Base-T			
Optional	WLAN 802.11a/b/g/n (Dual Band for 2.4 GHz/5 GHz) Bluetooth V2.1 EDR with MFi Certified, Serial Port (RS-232C)			
Accessories				
Optional	Full Cutter Module Partial Cutter Module Peel-off Module 8" External Media Stand Wireless LAN Kit Bluetooth Interface Kit Serial (RS-232C) I/F Kit AC Adapter Cover UHF Band RFID R/W Kit for BV410T Print Head Kit for Resolution Change			
Fonts Standard	Built-in Fonts: Bitmap, Outline, Price, TTF (Optional), Writable Characters			
Environmental				
Operating Temperatures	41°F - 104°F (5°C - 40°C)			
Operating Humidity	25% to 85% RH (Non-condensing)			
Storage Temperature/ Humidity	-40° to 60°C (-40° to 140°F) / 10 to 90% non-condensing relative humidity (RH)			
Power Consumption	Printing Mode: 60W Standby Mode: 4.4 W			
Power Supply	AC 100 to 240 V, 50/60 Hz			
Dimension (W x H x D)	7.9" x 10.5" x 7.8" (200 mm x 267 mm x 198.3 mm)			
Weight	6.4 lb. (2.9 kg)			
Weight Shipping	11.46 lb. (5.2 kg)			



business.toshiba.com

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation.

Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054
Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631
Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019
Tel: 678-546-9385

West Coast

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000